

Product Specification [产品规格书]:	Document No	PS-1601-01
Subject [主题]: 1.60mm MQS Series Terminal Specification	Date Issued	2023/07/12
	Date Revised	2023/07/12
	Version	A

This specification is referred to the 1.60mm MQS series Terminal

索引 【INDEX】

1. 适用范围 【Scope】
2. 规格与料号 【Spec and Part number】
3. 材质与表面处理 【Disposal of Material and surface】
4. 额定等级 【Ratings and applicable wires】
5. 性能测试 【 Performance 】



Product Specification [产品规格书]:	Document No	PS-1601-01
Subject [主题]: 1.60mm MQS Series Terminal Specification	Date Issued	2023/07/12
	Date Revised	2023/07/12
	Version	A

【1.适用范围 Scope】

此种规格包括 1.60mm MQS Series 端子连接器规格说明.

This Specification Covers the 1.60mm Series MQS Terminal Connector Specification.

【2.规格与料号 Spec and Part number】

规格内容 Specification	产品料号 Production No.	产品图示 Picture of Product
母端/ Female Terminal	1601TXF-PXXX	
公端/ Male Terminal	1601TXM-PXXX	

【3.材质与表面处理 Disposal of Material and surface】

规格内容 Specification	材质 Materials	表面处理 Disposal of Surface
Shell/Body	SUS 301	/
Contact	Copper Alloy	Tin Plated: 40~120u" (1~3μm)
PIN	Copper Alloy	Tin Plated: 40~120u" (1~3μm)

(上述参数请以工程图为准/Please Refer to the Project drawing for the above Specification)

【4. 额定等级 Ratings and applicable wires】

项目【Item】	规格【Standard】	
额定电流 Rated Current (Max.)	8A	[AC/DC]
使用温度范围 Ambient temperature Range	-40°C~+125°C	

【*升温时含端子.Including terminal temperature rise.】

Product Specification [产品规格书]:	Document No	PS-1601-01
Subject [主题]: 1.60mm MQS Series Terminal Specification	Date Issued	2023/07/12
	Date Revised	2023/07/12
	Version	A

【5.性能 PERFORMANCE】

测试内容 Item		规格要求 Specification requirements	参考标准 Reference standard																																																																																																
5-1	产品验收检查 Inspection of as-received condition	接触区域的体积电阻符合 DIN EN 60512-2-1 连接区域的体积电阻符合 DIN EN 60512-2-1 Visual inspection Contact resistance in contact area Crimp resistance	VW75174 Rev.2018 TG0																																																																																																
5-2	机械和热张弛特性 Mechanical and thermal relaxation behavior	根据 DIN EN 60512-1-1 进行目视检查 接触法向力测试, 确定法向接触力 热老化测试, 持续时间 1000H,然后在相应的时间 (1 小时、100 小时、200 小时、500 小时和 1 000 小时) 依次取出, 并测量法向力不能小于 1N。 Visual inspection /Contact normal force and Aging in dry heat	VW75174 Rev.2018 TG5																																																																																																
5-3	端子与线材间的引张强度 Conductor pull out strength	<table border="1"> <thead> <tr> <th rowspan="2">Cable cross-section (Cu)</th> <th colspan="5">Contact size in mm</th> </tr> <tr> <th>0.5</th> <th>0.63</th> <th>1.2 or 1.5</th> <th>2.8</th> <th>4.8</th> <th>9.5</th> </tr> </thead> <tbody> <tr> <td>0.35 mm²</td> <td colspan="5">50 N (75 N)</td> <td>-</td> </tr> <tr> <td>0.13 mm² (Cu/Mg)</td> <td colspan="5">60 N (85 N)</td> <td>-</td> </tr> <tr> <td>0.5 mm²</td> <td>-</td> <td colspan="3">85 N (105 N)</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.75 mm²</td> <td>-</td> <td colspan="3">108 N (125 N)</td> <td>140 N (162 N)</td> <td>-</td> </tr> <tr> <td>1.0 mm²</td> <td>-</td> <td>-</td> <td>150 N (180 N)</td> <td>150 N (180 N)</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.5 mm²</td> <td>-</td> <td>-</td> <td colspan="2">200 N (235 N)</td> <td>-</td> <td>-</td> </tr> <tr> <td>2.5 mm²</td> <td>-</td> <td>-</td> <td>-</td> <td>310 N (325 N)</td> <td>-</td> <td>-</td> </tr> <tr> <td>4.0 mm²</td> <td>-</td> <td>-</td> <td>-</td> <td>450 N</td> <td>450 N</td> <td>-</td> </tr> <tr> <td>6.0 mm²</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>500 N</td> <td>-</td> </tr> <tr> <td>10.0 mm²</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1 500 N</td> <td>-</td> </tr> <tr> <td>16.0 mm²</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1 900 N</td> <td>-</td> </tr> <tr> <td>25.0 mm²</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>1 900 N</td> </tr> </tbody> </table>	Cable cross-section (Cu)	Contact size in mm					0.5	0.63	1.2 or 1.5	2.8	4.8	9.5	0.35 mm ²	50 N (75 N)					-	0.13 mm ² (Cu/Mg)	60 N (85 N)					-	0.5 mm ²	-	85 N (105 N)			-	-	0.75 mm ²	-	108 N (125 N)			140 N (162 N)	-	1.0 mm ²	-	-	150 N (180 N)	150 N (180 N)	-	-	1.5 mm ²	-	-	200 N (235 N)		-	-	2.5 mm ²	-	-	-	310 N (325 N)	-	-	4.0 mm ²	-	-	-	450 N	450 N	-	6.0 mm ²	-	-	-	-	500 N	-	10.0 mm ²	-	-	-	-	1 500 N	-	16.0 mm ²	-	-	-	-	1 900 N	-	25.0 mm ²	-	-	-	-	-	1 900 N	VW71574 Rev.2018 TG10 Refer to : VW60330 and USCAR-21
Cable cross-section (Cu)	Contact size in mm																																																																																																		
	0.5	0.63	1.2 or 1.5	2.8	4.8	9.5																																																																																													
0.35 mm ²	50 N (75 N)					-																																																																																													
0.13 mm ² (Cu/Mg)	60 N (85 N)					-																																																																																													
0.5 mm ²	-	85 N (105 N)			-	-																																																																																													
0.75 mm ²	-	108 N (125 N)			140 N (162 N)	-																																																																																													
1.0 mm ²	-	-	150 N (180 N)	150 N (180 N)	-	-																																																																																													
1.5 mm ²	-	-	200 N (235 N)		-	-																																																																																													
2.5 mm ²	-	-	-	310 N (325 N)	-	-																																																																																													
4.0 mm ²	-	-	-	450 N	450 N	-																																																																																													
6.0 mm ²	-	-	-	-	500 N	-																																																																																													
10.0 mm ²	-	-	-	-	1 500 N	-																																																																																													
16.0 mm ²	-	-	-	-	1 900 N	-																																																																																													
25.0 mm ²	-	-	-	-	-	1 900 N																																																																																													
5-4	端子插入力与拔出力 Insertion and removal forces, mating cycle frequency	插入和拔出力, 无需额外润滑剂 Sn: 20 次插拔循环, Ag: 50 次插拔循环 Au: 100 次插拔循环 Mating and unmating forces /Mating cycles Sn: 20 mating cycles, Ag: 50 mating cycles , Au: 100 mating cycles. The insertion force may change by at most 25% compared to the initial value. The insertion and extraction forces must correspond to the drawing or the, product specification.	VW71574 Rev.2018 TG11																																																																																																

Product Specification [产品规格书]:	Document No	PS-1601-01
Subject [主题]: 1.60mm MQS Series Terminal Specification	Date Issued	2023/07/12
	Date Revised	2023/07/12
	Version	A

项 目 【Item】	条 件 【Test Condition】	规 格 【Requirement】
5-5 温升/降额 Current temperature rise, derating	<p>负载逐渐增加的电流并测量温升 要求: 测量值必须符合规格要求, 在降额图中标出以下内容: 测量值的 80% 特性曲线必须在图表中表示 (根据 DIN EN 60512-5-2), 电流是可以从 80 °C 环境温度下的降额曲线读取的电流.</p> <p>The 80-% characteristic curve of the measured values must be represented in the graph (as per DIN EN 60512-5-2). The nominal current is the current that can be read from the derating curve at 80 °C ambient temperature.</p>	VW71574 Rev.2018 TG12
5-6 热时间常数 Thermal time constant	<p>以 1/2/3/4/5 倍的额定电流加载触点并同时记录随时间推移的温度曲线, 直至稳定或达到最大值。 达到允许的温度。</p> <p>Loading of a contact with 1/2/3/4/5times the nominal current and simultaneous recording of the temperature curve over time until stabilization occurs or until the max. permissible component temperature is reached.</p>	VW71574 Rev.2018 TG14
5-7 电气压力测试 Electrical stress test	<p>对于试验前后的降额, 80°C环境温度下的载流能力相对于TG 启动时的降容变化不超过 20%。</p> <p>For the derating before and after the test, the current-carrying capacity at 80 °C ambient temperature may change by no more than 20% relative to the derating at the start of the TG.</p>	VW7157 4 Rev.2018 TG15

说明:

准备的样品应与适用于生产的说明一致, 应随机从当前生产中选择。