



Product Specification [产品规格书]:	Document No:	PS-2019-01
Subject [主题]:	Date Issued	2019/07/27
2.00mm Pitch 2019 Series Connector Specification	Date Revised	2022/09/02
	Version	E

This specification is referred to the 2.00mm series wire to board connector

索引【INDEX】

1. 适用范围【Scope】
2. 规格与料号【Spec and Part number】
3. 材质与表面处理【Disposal of Material and surface】
4. 额定等级【Ratings and applicable wires】
5. 性能【Performance】
 - 5-1. 电气的性能【Electrical Performance.】
 - 5-2. 机械的性能【Mechanical Performance】
 - 5-3. 环境性能及其它【Environmental Performance and Others】
6. 综合插入力及拔出力【Insertion/Withdrawal Force】
7. SMT 回流条件 SMT REFLOW CONDITION



Product Specification [产品规格书]:	Document No:	PS-2019-01
Subject [主题]:	Date Issued	2019/07/27
2.00mm Pitch 2019 Series Connector Specification	Date Revised	2022/09/02
	Version	E

【1.适用范围 Scope】

此种规格包括 2.00mm Pitch 2019 Series 连接器规格说明。

This Specification Covers the 2.00mm Pitch 2019 Series Connector Specification.

【2.规格与料号 Spec and Part number】

规格内容 Specification	产品料号 Production No.	产品图示 Picture of Product
端子/Terminal	2019T-XXSX-XXQ	
胶壳/Housing	2019H-1xXX-N0XBR01Q	
后塞/Retainer	C2019-1xXX-XXXBR01Q	
针座/Header	2000WVS-XXX-9TSW-S 2000WRS-XXX-9TSW-S	

【3.材质与表面处理 Material and surface treatment】

规格内容 Specification	材质 Materials	表面处理 Surface treatment
端子/Terminal	磷铜/Phosphor Bronze 高导电铜/High Conductivity Copper	Tin Plated: 2~5um(80~200u") Nickel Plated: 1~3 um(40~120u")
胶壳/Housing	PA66(UL 94V-0)	/
锁扣/Retainer	C2019-1x02~05:PBT/(UL 94V-0) C2019-1x06~15:PA4T/(UL 94V-0)	/
针座/ Header	Body	PA9T (UL 94V-0)
	PIN	黄铜/Brass
	Solder tab	黄铜/Brass

(上述参数请以工程图为准/Please Refer to the Project drawing for the above Specification)

【4. 额定等级 Ratings and applicable wires】

项目【Item】	规格【Standard】	
额定电压 Rated Voltage (Max.)	250V Max	[AC/DC]
额定电流 Rated Current (Max.)	3A Max	
使用温度范围 Ambient temperature Range	-40°C~+105°C (Phosphor Bronze) / -40°C~+125°C (High Conductivity Copper)	
适用线径 Applicable wire insulation O.D	20~24AWG(0.22~0.50mm ²)/ Insulation O.D. 1.60mm(Max.)	

【 *升温时含端子.Including terminal temperature rise. 】



Product Specification [产品规格书]:	Document No:	PS-2019-01
Subject [主题]:	Date Issued	2019/07/27
2.00mm Pitch 2019 Series Connector Specification	Date Revised	2022/09/02
	Version	E

【5.性能 PERFORMANCE】

5-1. 电气的性能 Electrical Performance.

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】
5-1-1	接触阻抗 Contact Resistance	公母配合,开放电压 20mV 以下,电流 10mA 检测连接器 A~B 区. Mate connectors, measure by dry circuit, 20mV MAX, 10mA. (Based upon EIA-364-06A).	Initial: 10 milliohms Max. After Test: 20 milliohms Max.
5-1-2	绝缘阻抗 Insulation Resistance	公母配合,在相邻端子,端子与地片之间,使用 500V 的直流电,检测连接器. Mate connectors, apply 500V DC between adjacent terminal or ground. (Based upon EIA-364-21B / MIL-STD-202 Method 302 Cond. B)	1000 Meg ohm Min.
5-1-3	耐电压 Dielectric Strength	公母配合,在相邻端子,端子与地片之间,使用 800V 的交流电 1 分钟,检测连接器. Mate connectors, apply 800V AC for 1 minute between adjacent terminal or ground. (Based upon EIA-364-20A / MIL-STD-202 Method 301)	没有击穿和电火花 No Breakdown and Flashover
5-1-4	铆线后端子接触阻抗 Contact resistance on crimped portion	铆线后之端子,开放电压 20mV 以下,电流 10mA 检测连接器. Crimp the applicable wire on to the terminal measure by dry circuit 20mV MAX, 10mA.	10 milliohms Max.
5-1-5	电压降落 Voltage Drop	在 75 或 100 毫米的点上,测量 12±1V 开路和 1±0.05A 短路的电压降,在 75 或 100 毫米的短电路中。从总电阻中减去导线电阻。 Measure voltage drop by 12±1V of open circuit and 1±0.05A of short circuit at the 75 or 100mm of point from crimped section. Subtract wire conductor resistance from total resistance.	10mV/A Max



Product Specification [产品规格书]:	Document No:	PS-2019-01
Subject [主题]:	Date Issued	2019/07/27
2.00mm Pitch 2019 Series Connector Specification	Date Revised	2022/09/02
	Version	E

5-2. 机械的性能 Mechanical Performance.

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】
5-2-1	插拔力 Insertion & withdraw Force	以每分钟 50mm 的速率插入和拔出。 Insert and withdraw Connectors at the speed rate of 50mm/minute.	参照第 6 项 Refer to paragraph 6
5-2-2	端子保持力 Terminal/ Housing Retention Force	以每分 50mm 的速率,将端子从 Housing 内轴向拔出的力量。 Apply axial pull out force at the speed rate of 50mm/minute on the terminal assembled in the housing.	Primary Lock : 20N {2.04kgf} Min.
			Primary + Secondary Lock 45N {4.59kgf} Min.
5-2-3	端子插入力 Terminal Insertion Force	铆线后之端子插入 Housing 所需最大力量。 Insert the crimped terminal into the housing.	9.8N {1.0kgf} Max.
5-2-4	Pin 针保持力 Pin Retention Force	以每分 100mm 的速率,将 PIN 针从 Header 内轴向拔出 的力量。 Apply axial push force at the speed rate of 100mm/minute.	30N {3.06kgf} min.



Product Specification [产品规格书]:	Document No:	PS-2019-01
Subject [主题]:	Date Issued	2019/07/27
2.00mm Pitch 2019 Series Connector Specification	Date Revised	2022/09/02
	Version	E

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】			
5-2-5	端子压着强度 Tensile strength (Crimped connections)	固定铆线后的端子，使电线与端子分离时所需的最小力量,(绝缘铆爪打开). Fix the crimped terminal, apply axial pull out force on the wire. (Measure without insulation crimp).	AWG#	20#	22#	24#
			(FLR)	(0.50mm ²)	(0.35mm ²)	0.22mm ²
			Spec Min. N	50N (75N) ^{a)}	50N (75N) ^{a)}	50N
			a) If for production reasons, the conductor pull-out strength is measured with insulation crimp, the values in parentheses apply. (Refer to VW60330)			
5-2-6	Lock 保持力 Lock Retention Force	将插好端子的公母座含卡扣以每分钟 50mm 的速度拔出所需要力量。 Mate connectors and apply pull-out force at the speed rate of 50mm/min .This Test should be done with positive lock locked.	2-Circuit product 40N MIN 3 to 6p-Circuit product 50N MIN 7 to 15P-Circuit product 60N MIN			

5-3. 环境性能及其它 Environmental Performance and Others.

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】	
5-3-1	重复插拔 Repeated Insertion/Withdrawal	以每分钟不超过 10 次的速率,将公母插拔 30 次。 When mated up to 30 cycles repeatedly by the rate of 10 cycles per minute.	接触阻抗 Contact Resistance	20 milliohms Max.
5-3-2	温升测试 Temperature Rise	公母连接器配合后,加载额定电流直到温度上升到稳定状态,然后再测量温升(EIA364-70, Method 1) Mating connectors shall be energized at rating current until thermal stability is achieved, and then measured the temperature rise(EIA364-70, Method 1)	温升测试 Temperature rise	30°C Max.
5-3-3	耐振动性 Vibration	振幅: 1.5mm P-P 时间: 20~200~20 Hz in 3minute 持续时间: 每轴向 3 小时 加速度: 44m/S ² 开放电压: 20mV 以下 开放电流: 10mA 以下 Amplitude: 1.5mm P-P Sweep time: 20~200~20 Hz in 3 minute Duration: 3 hours in each X.Y.Z axial. (Based upon EIA-364-28B/MIL-STD-202 Method 213B Cond. A)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
			电压降落 Voltage Drop	20mV/A Max
			瞬断 Discontinuity	1 micro-second Max.



Product Specification [产品规格书]:	Document No:	PS-2019-01
Subject [主题]:	Date Issued	2019/07/27
2.00mm Pitch 2019 Series Connector Specification	Date Revised	2022/09/02
	Version	E

5-3-4	耐冲击性 Shock	在 X.Y.Z 上 6 个方向上,以 981m/s ² (100G 的力量)冲击下各 3 回. 作用时间: 6ms 981m/s ² {100G}, 3 strokes in each X.Y.Z. axes. Operation time:6ms (Based upon EIA-364-27B/MIL-STD-202 Method 213B Cond. A)	外观 Appearance	无异状 No Damage
			瞬断 Discontinuity	1 micro-second Max.

项 目 【Item】		条 件 【Test Condition】	规 格 【Requirement】	
5-3-5	耐热性 Heat Resistance	125±2°C,96 hours. (Based upon MIL-STD-202 Method 108A Cond. A)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
5-3-6	耐寒性 Cold Resistance	-40±3°C,96 hours. (Based upon EIA-364-105)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
5-3-7	耐湿性 Humidity	温度: 60±2°C 湿度: 90~95%(RH) 持续时间: 96 hours Temperature: 60±2°C Relative Humidity: 90~95% Duration: 96 hours (Based upon EIA-364-31A/MIL-STD-202 Method 103B Cond.B)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
			耐电压 Dielectric Strength	Must meet 5-1-3
			绝缘阻抗 Insulation Resistance	500 Megohm Min.
5-3-8	温度变化 Temperature Cycling	从-40°C持续 30 分钟升至+125°C持续 30 分钟,循环 5 次. 5 cycles of: a) -40°C 30 minutes. b) +125°C 30 minutes. (Based upon EIA-364-32B)	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
			电压降落 Voltage Drop	20mV/A Max



Product Specification [产品规格书]:			Document No:	PS-2019-01
Subject [主题]:			Date Issued	2019/07/27
2.00mm Pitch 2019 Series Connector Specification			Date Revised	2022/09/02
			Version	E
			公母座带卡扣保持力 Housing/Header Retention Force	满足 5-2-6 Must meet 5-2-6
			端子与 HSG 保持力 Terminal/Housing Retention Force	满足 5-2-2 Must meet 5-2-2
5-3-9	盐水喷雾 Salt Spray	在温度 35±2°C, 盐水浓度 5±1% 下, 盐水喷雾 48±1 小时. 48±1 hours exposure to a salt spray from the 5±1% solution at 35±2°C. (Based upon EIA-364-26B/MIL-STD-202 Method 101D Cond.B).	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
5-3-10	耐亚硫酸腐蚀性 SO ₂ gas	将公母对插好的样品放入温度 40±2°C, 亚硫酸浓度在 50±5ppm 环境中放置 24 小时。 24 Hours exposure to 50±5ppm SO ₂ gas at 40±2°C	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
5-3-11	焊锡性 Solder- Resistance	焊接时间: 3~5 秒. 焊接温度: 245±5°C. Soldering time: 3~5sec solder. Temperature: 245±5°C.	浸锡性 Solder Wetting	浸渍面积需 90% 以上 90% of immersed area must show no voids, pin holes.
5-3-12	焊锡耐热性 Resistance to Soldering Heat	将恒温烙铁温度调整至 350±5°C, 将熔融状态的锡焊料按压在 PIN 脚 3 秒。 Press the solder trowel of 350±5°C for 3sec	外观 Appearance	无异状 No Damage
			接触阻抗 Contact Resistance	20 milliohms Max.
WRITTEN BY: Alan qin			APPROVED BY: Kim Huang	
			Sheet: 7 of 8	




Product Specification [产品规格书]:	Document No:	PS-2019-01
Subject [主题]:	Date Issued	2019/07/27
2.00mm Pitch 2019 Series Connector Specification	Date Revised	2022/09/02
	Version	E

【6.综合插入力及拔出力 INSERTION/WITHDRAWAL FORCE】 <Connector mating force>

PIN 数 No. of CKT	初次插入力(最大值) First Insertion (kgf Max.)	30 次拔出力(最小值) 30 th Withdrawal (kgf Min.)	PIN 数 No. of CKT	初次插入力(最大值) First Insertion (kgf Max.)	30 次拔出力(最小值) 30 th Withdrawal (kgf Min.)
Single	/	/	09	4.4	0.90
02	1.5	0.20	10	4.7	1.00
03	2.0	0.30	11	5.0	1.10
04	2.5	0.40	12	5.3	1.20
05	3.0	0.50	13	5.6	1.30
06	3.5	0.60	14	6.0	1.40
07	3.8	0.70	15	6.4	1.50
08	4.1	0.80	16	6.8	1.60

注：以上插拔次数为 30 次 Note: Insertion and Withdrawal for 30Cycles

【7. SMT 回流条件 SMT REFLOW CONDITION】



温度条件曲线图/ 基板上温度

TEMPERATURE CONDITION GRAPH/ (TEMPERATURE ON BOARD PATTERN SIDE)

注记：由于 P.C 板等焊接装置改变条件,所以请预先用自己的装置检查回流焊的条件。

Notes: Please check the reflow soldering condition by your own devices beforehand. Because the condition changes by the soldering devices, P.C. boards, and so on.